

■ 一段式 フレーム別仕様一覧表

型式	仕様	最大積載 (kg)	ストローク (mm)	テーブル寸法 O1サイズ (mm)	台盤寸法 (mm)	最低高さ (mm)	最高高さ (mm)	シリンダー (φ×本)	シリンダー ストローク	上昇速度	上昇時間目安 (st/sec)		電動機 (kW)	ユニット型式	ポンプ	タンク (リッター)	必要油量	本体重量
											50Hz	60Hz						
TH 1-0306A		300kg	600	600×1,050	570×1,000	150	750	φ70×1	120st	LOW	18	15	0.55	5-1-1 140	PA1	1.3	0.46	149
										HIGH	10	8	0.55	5-2-1 140	PA2			
TH 1-0312A		300kg	1,200	700×1,710	680×1,690	165	1,365	φ70×1	230st	LOW	34	29	0.55	5-1-1 140	PA1	1.3	0.88	240
										HIGH	18	15	0.55	5-2-1 140	PA2			
TH 1-0506A		500kg	600	600×1,050	570×1,000	150	750	φ70×1	120st	LOW	18	15	0.55	5-1-1 140	PA1	1.3	0.46	162
										HIGH	10	8	0.55	5-2-1 140	PA2			
TH 1-0508A		500kg	845	610×1,360	570×1,198	155	1,000	φ70×1	150st	LOW	23	19	0.55	5-1-1 140	PA1	1.3	0.57	193
										HIGH	12	10	0.55	5-2-1 140	PA2			
TH 1-0512A		500kg	1,250	720×2,000	700×1,856	200	1,450	φ80×1	230st	LOW	24	20	0.7	7-2-3 140	PA2	3	1.16	346
										HIGH	16	13	1.13	11-3-3 140	PA3			
TH 1-0706A		700kg	600	600×1,050	570×1,000	155	755	φ80×1	120st	LOW	23	20	0.55	5-1-1 140	PA1	1.3	0.60	180
										HIGH	12	10	0.55	5-2-1 140	PA2			
TH 1-1004C		1,000kg	450	900× 850	880× 830	150	600	φ80×2	90st	LOW	35	29	0.55	5-1-1 140	PA1	1.3	0.90	200
										HIGH	18	15	0.55	5-2-1 140	PA2			
TH 1-1006A		1,000kg	600	600×1,050	570×1,000	155	755	φ70×2	120st	LOW	36	30	0.55	5-1-1 140	PA1	1.3	0.92	199
										HIGH	19	16	0.55	5-2-1 140	PA2			
TH 1-1006B		1,000kg	600	900×1,050	800×1,000	155	755	φ70×2	120st	LOW	36	30	0.55	5-1-1 140	PA1	1.3	0.92	212
										HIGH	19	16	0.55	5-2-1 140	PA2			
TH 1-1008A		1,000kg	845	610×1,360	570×1,198	155	1,000	φ70×2	150st	LOW	45	38	0.55	5-1-1 140	PA1	1.3	1.15	215
										HIGH	24	20	0.55	5-2-1 140	PA2			
TH 1-1008B		1,000kg	845	900×1,360	800×1,198	155	1,000	φ70×2	150st	LOW	45	38	0.55	5-1-1 140	PA1	1.3	1.15	240
										HIGH	24	20	0.55	5-2-1 140	PA2			
TH 1-1012A		1,000kg	1,250	800×2,000	700×1,856	200	1,450	φ70×2	230st	LOW	36	30	0.7	7-2-3 140	PA2	3	1.77	364
										HIGH	24	20	1.13	11-3-3 140	PA3			
TH 1-1012B		1,000kg	1,250	1,100×2,000	1,000×1,856	200	1,450	φ70×2	230st	LOW	36	30	0.7	7-2-3 140	PA2	3	1.77	406
										HIGH	24	20	1.13	11-3-3 140	PA3			
THD 1-1504A		1,500kg	400	650×1,000	610× 975	220	620	φ90×1	100st	LOW	25	21	0.55	5-1-1 140	PA1	1.3	0.64	250
										HIGH	13	11	0.55	5-2-1 140	PA2			
TH 1-1504C		1,500kg	400	900× 850	830× 814	220	620	φ80×2	90st	LOW	35	30	0.55	5-1-1 140	PA1	1.3	0.90	255
										HIGH	19	16	0.55	5-2-1 140	PA2			
THD 1-1509A		1,500kg	900	620×1,620	600×1,475	220	1,120	φ80×2	190st	LOW	39	33	0.7	7-2-3 140	PA2	3	1.91	356
										HIGH	26	22	1.13	11-3-3 140	PA3			
THD 1-1510A		1,500kg	1,000	900×1,500	850×1,475	220	1,220	φ80×2	190st	LOW	39	33	0.7	7-2-3 140	PA2	3	1.91	441
										HIGH	26	22	1.13	11-3-3 140	PA3			
THD 1-1512A		1,500kg	1,250	800×2,000	700×1,856	220	1,470	φ80×2	230st	LOW	47	39	0.7	7-2-3 140	PA2	3	2.31	471
										HIGH	32	27	1.13	11-3-3 140	PA3			
TH 1-2004A		2,000kg	400	800×1,100	750× 975	220	620	φ80×2	90st	LOW	35	30	0.55	5-1-1 140	PA1	1.3	0.90	301
										HIGH	19	16	0.55	5-2-1 140	PA2			
TH 1-2004C		2,000kg	400	900× 850	830× 814	220	620	φ80×2	90st	LOW	35	30	0.55	5-1-1 140	PA1	1.3	0.90	241
										HIGH	19	16	0.55	5-2-1 140	PA2			
THD 1-2009A		2,000kg	900	620×1,620	600×1,475	220	1,120	φ90×2	190st	LOW	49	41	0.7	7-2-3 140	PA2	3	2.42	374
										HIGH	33	28	1.13	11-3-3 140	PA3			
THD 1-2010A		2,000kg	1,000	900×1,500	850×1,475	220	1,220	φ90×2	190st	LOW	49	41	0.7	7-2-3 140	PA2	3	2.42	441
										HIGH	33	28	1.13	11-3-3 140	PA3			
THD 1-2012A		2,000kg	1,250	1,000×2,000	700×1,856	220	1,470	φ90×2	230st	LOW	60	50	0.7	7-2-3 140	PA2	3	2.92	511
										HIGH	40	34	1.13	11-3-3 140	PA3			
THD 1-2015A		2,000kg	1,500	1,120×2,400	1,100×2,300	300	1,800	φ90×2	275st	LOW	48	40	1.13	11-3-6 140	PA3	6	3.50	823
										HIGH	24	20	2.2	22-5-6 140	PA5			
THD 1-3012A		3,000kg	1,250	1,000×2,000	850×1,962	270	1,520	φ110×2	230st	LOW	60	50	1.13	11-3-6 140	PA3	6	4.37	696
										HIGH	30	25	2.2	22-5-6 140	PA5			
THD 1-3015A		3,000kg	1,500	1,200×2,400	1,100×2,300	300	1,800	φ110×2	275st	LOW	72	60	1.13	11-3-6 140	PA3	6	5.22	933
										HIGH	36	30	2.2	22-5-6 140	PA5			