

T-14, T-2 4t受枠仕様 充填深さ 70/40mm

溝幅 (mm)	呼称	本体寸法					適用荷重		受枠				
							T-14	T-2					
		h ₁	W	W ₁	L	h	質量(kg/ 枚)	質量(kg/ 枚)	アングルサイズ	A	A ₁	H	質量 (kg/両側m)
100	710	70	188	180	599	105	7.4	6.7	L112×50×4t	200	280	112	10.5
	410	40				75	5.7	5.1	L82×50×4t			82	8.6
150	715	70	238	230		105	8.3	7.6	L112×50×4t	250	330	112	10.5
	415	40				75	6.6	5.8	L82×50×4t			82	8.6
200	720	70	288	280		105	9.3	8.4	L112×50×4t	300	380	112	10.5
	420	40				75	7.4	6.6	L82×50×4t			82	8.6
250	725	70	338	330		105	10.3	9.3	L112×50×4t	350	430	112	10.5
	425	40				75	8.3	7.3	L82×50×4t			82	8.6
300	730	70	388	380		105	11.2	10.1	L112×50×4t	400	480	112	10.5
	430	40				75	9.2	8.1	L82×50×4t			82	8.6
350	735	70	438	430		105	14.9	11.0	L112×50×4t	450	530	112	10.5
	435	40				75	12.8	8.8	L82×50×4t			82	8.6
400	740	70	488	480		105	19.2	11.8	L112×50×4t	500	580	112	10.5
	440	40				75	16.9	9.6	L82×50×4t			82	8.6


T-14, T-2 3t受枠仕様 充填深さ 70/40mm

溝幅 (mm)	呼称	本体寸法					適用荷重		受枠				
							T-14	T-2					
		h ₁	W	W ₁	L	h	質量(kg/ 枚)	質量(kg/ 枚)	アングルサイズ	A	A ₁	H	質量 (kg/両側m)
100	710	70	190	182	599	105	7.4	6.8	L111×50×3t	200	280	111	8.1
	410	40				75	5.7	5.1	L81×50×3t			81	6.7
150	715	70	240	232		105	8.4	7.6	L111×50×3t	250	330	111	8.1
	415	40				75	6.6	5.9	L81×50×3t			81	6.7
200	720	70	290	282		105	9.3	8.5	L111×50×3t	300	380	111	8.1
	420	40				75	7.4	6.6	L81×50×3t			81	6.7
250	725	70	340	332		105	10.3	9.3	L111×50×3t	350	430	111	8.1
	425	40				75	8.3	7.4	L81×50×3t			81	6.7
300	730	70	390	382		105	11.2	10.2	L111×50×3t	400	480	111	8.1
	430	40				75	9.2	8.1	L81×50×3t			81	6.7
350	735	70	440	432		105	14.9	11.0	L111×50×3t	450	530	111	8.1
	435	40				75	12.8	8.9	L81×50×3t			81	6.7
400	740	70	490	482		105	19.2	11.9	L111×50×3t	500	580	111	8.1
	440	40				75	17.0	9.6	L81×50×3t			81	6.7

歩道用 充填深さ 70/30mm


溝幅 (mm)	呼称	本体寸法					適用荷重		受枠				
		h ₁	W	W ₁	L	h	歩道		アングルサイズ	A	A ₁	H	質量 (kg/両側m)
質量(kg/枚)													
100	710	70	190	182	599	94	6.4		L100×50×3t	200	280	100	7.6
	310	30				54	4.1		L60×50×3t			60	5.7
150	715	70	240	232		94	7.2		L100×50×3t	250	330	100	7.6
	315	30				54	4.7		L60×50×3t			60	5.7
200	720	70	290	282		94	8.0		L100×50×3t	300	380	100	7.6
	320	30				54	5.4		L60×50×3t			60	5.7
250	725	70	340	332		94	8.8		L100×50×3t	350	430	100	7.6
	325	30				54	6.0		L60×50×3t			60	5.7
300	730	70	390	382		94	9.6		L100×50×3t	400	480	100	7.6
	330	30				54	6.7		L60×50×3t			60	5.7
350	735	70	440	432		94	10.4		L100×50×3t	450	530	100	7.6
	335	30				54	7.3		L60×50×3t			60	5.7
400	740	70	490	482		94	11.2		L100×50×3t	500	580	100	7.6
	340	30				54	8.0		L60×50×3t			60	5.7

PB-14/PB-2




部品構成 材質:SUS304

- ①底波板 ②受枠
③アンカー ④ゴムクッション(NR)




PB-歩



部品構成 材質:SUS304

- ①底波板 ②受枠
③アンカー ④ゴムクッション(NR)



●適用荷重の表記について、歩(歩道用)はT-2未満です。●規格外サイズ・異形・特殊仕様の設計、製作も承ります。●ご注意：みぞぶた本体の質量は定尺599mmの数値です。