

T-14, T-2 4t四L受枠仕様 充填深さ 70/40mm


ます穴 (mm)	呼称	本体寸法					適用荷重		四L受枠					
		h ₁	W	W ₁	L	h	T-14		アングルサイズ	A	A ₁	B	H	質量 (kg/ 両側m)
							質量(kg/ 枚)	質量(kg/ 枚)						
300×300	730	70	388	380	388	105	8.9	7.8	L112×50×3t	400	480	400	112	8.1
	430	40				75	7.1	6.0	L82×50×3t				82	6.5
350×350	735	70	438	430	438	105	10.6	9.0	L112×50×3t	450	530	450	112	9.1
	435	40				75	8.7	7.1	L82×50×3t				82	7.4
400×400	740	70	488	480	488	105	12.1	10.7	L112×50×3t	500	580	500	112	10.1
	440	40				75	10.0	8.6	L82×50×3t				82	8.2
450×450	745	70	538	530	538	105	14.1	12.1	L112×50×3t	550	630	550	112	11.1
	445	40				75	11.8	9.8	L82×50×3t				82	9.0
500×500	750	70	588	580	588	105	19.9	16.8	L112×50×3t	600	680	600	112	12.1
	450	40				75	17.4	14.4	L82×50×3t				82	9.9
550×550	755	70	638	630	638	105	22.2	19.6	L112×50×3t	650	730	650	112	13.2
	455	40				75	19.5	17.0	L82×50×3t				82	10.7
600×600	760	70	688	680	688	105	25.4	21.9	L112×50×3t	700	780	700	112	14.2
	460	40				75	22.6	19.1	L82×50×3t				82	11.5

T-14, T-2 3t四L受枠仕様 充填深さ 70/40mm

ます穴 (mm)	呼称	本体寸法					適用荷重		四L受枠					
		h ₁	W	W ₁	L	h	T-14		アングルサイズ	A	A ₁	B	H	質量 (kg/ 両側m)
							質量(kg/ 枚)	質量(kg/ 枚)						
300×300	730	70	390	382	390	105	8.9	7.8	L111×50×3t	400	480	400	111	6.2
	430	40				75	7.2	6.1	L81×50×3t				81	5.1
350×350	735	70	440	432	440	105	10.7	9.0	L111×50×3t	450	530	450	111	7.0
	435	40				75	8.7	7.1	L81×50×3t				81	5.7
400×400	740	70	490	482	490	105	12.1	10.8	L111×50×3t	500	580	500	111	7.8
	440	40				75	10.0	8.7	L81×50×3t				81	6.3
450×450	745	70	540	532	540	105	14.1	12.2	L111×50×3t	550	630	550	111	8.5
	445	40				75	11.8	9.9	L81×50×3t				81	7.0
500×500	750	70	590	582	590	105	19.9	16.9	L111×50×3t	600	680	600	111	9.3
	450	40				75	17.5	14.4	L81×50×3t				81	7.6
550×550	755	70	640	632	640	105	22.3	19.7	L111×50×3t	650	730	650	111	10.1
	455	40				75	19.6	17.0	L81×50×3t				81	8.2
600×600	760	70	690	682	690	105	25.5	22.0	L111×50×3t	700	780	700	111	10.9
	460	40				75	22.7	19.2	L81×50×3t				81	8.9


歩道用 充填深さ 70/30mm

ます穴 (mm)	呼称	本体寸法					適用荷重		四L受枠					
		h ₁	W	W ₁	L	h	歩道		アングルサイズ	A	A ₁	B	H	質量 (kg/ 両側m)
							質量(kg/ 枚)	質量(kg/ 枚)						
300×300	730	70	390	382	390	94	7.4	7.4	L100×50×3t	400	480	400	100	5.8
	330	30				54	4.9	4.9	L60×50×3t				60	4.3
350×350	735	70	440	432	440	94	8.5	8.5	L100×50×3t	450	530	450	100	6.5
	335	30				54	5.8	5.8	L60×50×3t				60	4.8
400×400	740	70	490	482	490	94	10.1	10.1	L100×50×3t	500	580	500	100	7.2
	340	30				54	7.1	7.1	L60×50×3t				60	5.3
450×450	745	70	540	532	540	94	11.4	11.4	L100×50×3t	550	630	550	100	8.0
	345	30				54	8.2	8.2	L60×50×3t				60	5.9
500×500	750	70	590	582	590	94	12.9	12.9	L100×50×3t	600	680	600	100	8.7
	350	30				54	9.4	9.4	L60×50×3t				60	6.4
550×550	755	70	640	632	640	94	14.7	14.7	L100×50×3t	650	730	650	100	9.4
	355	30				54	10.9	10.9	L60×50×3t				60	6.9
600×600	760	70	690	682	690	94	16.3	16.3	L100×50×3t	700	780	700	100	10.1
	360	30				54	12.3	12.3	L60×50×3t				60	7.5


PBO-14
PBO-2

部品構成 材質:SUS304

- ①底波板 ②受枠
③アンカー ④ゴムクッション(NR)




PBO-歩



部品構成 材質:SUS304

- ①底波板 ②受枠
③アンカー ④ゴムクッション(NR)



●適用荷重の表記について、歩(歩道用)はT-2未満です。●規格外サイズ・異形・特殊仕様の設計、製作も承ります。